UNCLASSIFIED

AD NUMBER AD438821 LIMITATION CHANGES TO: Approved for public release; distribution is unlimited. FROM: Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; MAR 1964. Other requests shall be referred to Office of Naval Research Washington, DC 20360. AUTHORITY onr ltr, 4 may 1977

THIS REPORT HAS BEEN DELIMITED

AND CLEARED FOR PUBLIC RELEASE

UNDER DOD DIRECTIVE 5200.20 AND

NO RESTRICTIONS ARE IMPOSED UPON

ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

UNCLASSIFIED AD 4 3 8 8 2 1

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

4 3 8 8 2 1

W

00

3

4

TYCO LABORATORIES, INC.

BEAR HILL, WALTHAM 54, MASSACHUSETTS
AREA CODE 617
TELEPHONE 899-1650

ELECTROCHEMISTRY OF FUEL CELL ELECTRODES

by

A. C. Makrides Principal Investigator

Semi-Annual Technical Summary Report covering period through March 30, 1964

Contract No. Nonr-3765(00) dated April 16, 1962 as amended expiring April 15, 1965

ARPA ORDER No. 302-62 Project Code 9800 Task No. NR 359-443

prepared for:

OFFICE OF NAVAL RESEARCH Materials Sciences Division Washington 25, D. C.

I. INTRODUCTION

The objective of this program is to clarify the molecular basis of electrocatalysis and thereby to provide the necessary scientific framework for the optimization of fuel cell electrodes. Using electrodes of varied chemical composition, we have attempted to show whether their catalytic properties depend primarily upon the intrinsic chemical activity of the individual surface atoms, or upon the energy states of the crystal as a whole. If this distinction can be made, and if quantitative correlations with the atomic or continuum properties can be established, then the design of fuel cell electrodes becomes enormously simplified.

Hydrogen oxidation and reduction, the reduction of oxygen, and the oxidation of formic acid, a soluble organic substance, have been selected for these studies because of their relevance to fuel cell systems and because of their relative simplicity. The electrodes used range from amalgams to III-V semiconducting compounds. The approach is to resolve the over-all reaction on any given electrode into the elementary steps of adsorption, electron transfer, chemical combination of free radicals, etc., and to determine how the parameters governing the rates of these various steps are related to the electrode composition and structure. The experimental studies currently under way are described below.

II. ELECTROCATALYSIS BY AMALGAM ELECTRODES

The question of whether the continuum properties or the atomic nature of an electrode determines its electrocatalytic properties can be approached directly by using amalgam electrodes. The high overpotential for the hydrogen evolution reaction on mercury makes it easy to detect the effect of catalytic additives. A clean, reproducible surface can be achieved with liquid amalgams by using a dropping electrode; thus, this technique was adopted in our studies.

The first systems investigated were Pt-Hg and Pd-Hg. The results of these studies are given briefly in the last quarterly report and are reported in Technical Memorandum No. 7. It was found that Pt and Pd in solution in Hg have substantially different catalytic properties than bulk Pt and Pd; it was concluded that electrocatalysis in this particular system is primarily a cooperative property and that the behavior of a metal atom is drastically influenced by its environment.

The In-Hg system was investigated in some detail during the past six months (Technical Memoranda No. 9 and 10). This particular system had the advantage of a wide solubility range (up to 70 at % In at room temperature). Three types of studies were carried out: a) thermodynamic data (activities) for In-Hg were obtained by emf measurements, b) the kinetics of the hydrogen reaction on In-Hg amalgams and on pure In were studied, and c) the double layer structure on In-Hg amalgams was studied by capacity measurements.

Activity coefficients for indium and mercury in their liquid amalgams at 25^{o}C were calculated from measurements of emf in a cell without liquid junctions. Within experimental error, the results were described by the empirical equation \log_{10} % $_{In}$ = 1.54 (1 - $\rm X_{Hg})^2$, where % $_{In}$ is the activity coefficient of In referred to infinite dilution, and $\rm X_{Hg}$ is the rude fraction of mercury. The activity of pure solid indium is 21.6 on the same scale. The excess entropy of the mixtures was found to be nearly zero. The standard potential of the $\rm In^{+3}$ - In couple was - 335.0 mv at $\rm 25^{o}C$.

The rate of the hydrogen evolution reaction was studied on dropping indium amalgam electrodes containing 0 to 65% In in 0.1. M $\rm HClO_4$ at $25^{\rm O}\rm C$. The potential of zero charge for the same series of amalgams was also determined. The Frumkin correction for the potential drop across the diffuse double layer was used to obtain the exchange current and transfer coefficient for each of the amalgams. The exchange current increased by approximately a factor of ten as the composition varied from 0 to 65% In. Within experimental error the transfer coefficient was 0.50, independent of composition. The current at the zero-charge potential, which gives a measure of the free energy of activation for the discharge reaction, increases by a factor of 10^4 as the composition varies from 0 to 65% In . The corresponding decrease in the free energy of activation is approximately 5 kcal/mol, and is attributed primarily to a change of work function.

Capacity measurements were also obtained for these amalgams over the same concentration range in 0.1 M $\rm HClO_4$. These measurements are being extended to LiF and HCl solutions. The results will be analyzed when they are complete.

Measurements of the hydrogen overpotential on pure In, including temperature coefficients, were also carried out and will be reported as soon as they are analyzed in detail.

III. ELECTROCHEMISTRY OF III-V SEMICONDUCTING COMPOUNDS

Binary compounds crystallizing in the zincblende or wurtzite structures show two (111) surfaces of different composition. In the case of GaAs, opposite (111) surfaces are composed only of Ga atoms or As atoms. This property of III-V compounds permits the study of the electrocatalytic activity of two chemically different surfaces of the same crystal.

It was found that p-type and n-type gallium arsenide behave anodically in the same way as p- and n-type germanium; the anodic current on n-type material reaches a limiting current which is controlled by the diffusion of holes from the bulk of the semiconductor; the anodic current on p-type material increases with potential until a surface oxide is formed.

The dissolution behavior of p-type gallium arsenide and p-type gallium antimonide indicates the formation, at positive potential, of arsenic and antimony surface oxides.

Current-potential measurements on the gallium surfaces of n- and p-type gallium arsenide and p-type gallium antimonide are very close, and, at high overpotentials, very similar to measurements on pure gallium.

Current-potential curves on the antimony surfaces of gallium and indium antimonide are very nearly the same, and differ only by about 60 mv from those on the gallium surface. The overpotentials on the antimony surfaces are, however, higher than on pure antimony by some 150 mv.

IV. OXYGEN REDUCTION AND OXIDE FORMATION

Most metals form stable surface oxides in the potential range where oxygen can be reduced. Therefore, a study of the electrochemical properties of surface oxides is a necessary step in any detailed study of the mechanism of oxygen reduction.

A study of the galvanostatic reduction in N $HClO_4$ of gold surface oxides formed potentiostatically at various potentials was completed (Technical Memorandum No. 6) during the report period. Oxides formed at 1.2 to 1.8 v vs. H^+/H_2 were reduced at current densities varying between 10 and 1000 $\rm a/cm^2$ in molar perchlorate solutions of pH 0.04 to 2.1. It was found that the extent of oxide formation is determined by the potential of anodization, the charge increasing linearly with the potential of formation in the range of 1.4 to 1.8 v. Cathodic chronopotentiograms showed that the reduction of the oxide occurs at a definite potential which depends on the cathodic current density. Current-potential curves, constructed from the cathodic chronopotentiograms, followed a Tafel relation with a slope of 41 mv. The exchange current for oxide reduction decreased with pH and with increasing potential of formation of the oxide. The electrochemical order of the reaction was 1.4 with respect to pH. These results were interpreted in terms of a reaction scheme in which the reduction of an intermediate (Λu^{+2}) is the slow step in the over-all process.

Some studies of "aging" of potentiostatically-formed oxides have also been carried out during this period. Both galvanostatic and voltammetric reduction techniques were employed. It was found that although the oxide grows very rapidly (viz. 95% of its final, steady-state thickness in 1 sec), its reduction characteristics continued to change appreciably over long periods. Some changes are still observable 5 min. after formation. The origin of these changes is not clear at present.

Further experiments with this system showed that certain cations in solution, viz. ${\rm Mg}^{+2}$, considerably alter the kinetics of reduction of the oxide; however, the amount of oxide at any given potential is essentially unaltered. These effects are probably associated with cation adsorption which modifies the double layer structure.

V. ELECTROCATALYTIC OXIDATION OF FORMIC ACID

The adsorption and oxidation of formic acid on smooth Pt electrodes was studied in ${\rm HClO}_4$ solutions by anodic and cathodic chronopotentiometry and by potentiostatic, steady-state techniques (Technical Memorandum No 8). The oxidation rate at each potential was determined as a function of electrode preparation, pH , and formic acid concentration. Anodic pre-treatment activates an electrode for the subsequent oxidation of HCOOH . However, the oxidation rate at any given potential declines with time because of the slow adsorption of a substance which interferes with the subsequent oxidation of HCOOH . The kinetics of adsorption and the extent of adsorption of the blocking substance were determined at a series of potentials. The equilibrium adsorption decreases with potential above 0.35 v and is essentially zero at 0.70 v .

The rate of oxidation of HCOOH is first order with respect to the free surface, the HCOOH concentration, and the pH . The oxidation rate increases with potential according to a Tafel type relation (slope ~ 60 mv) up to potentials of about 0.4 v , but is independent of potential thereafter. The current plateau is not controlled by diffusion. A mechanism for oxidation is suggested in which the slow step is a non-electrochemical, dissociative reaction of HCOOH .

Currently, an experimental study of large anodic galvanostatic transients is in progress in order to identify the poisoning adsorbate on the electrode. This study involves the reversal of the current during oxidation of the adsorbate, which makes it possible to determine how much of the current passed is effective in oxidizing adsorbed material and how much goes in side processes. The side processes are oxidation of the electrode itself and oxidation of unadsorbed formic acid diffusing to the electrode surface.

Present results show a clean separation of these processes. Thus, at low current densities ($\sim 8~\text{ma/cm}^2~\text{in}~1~\text{M}~\text{HCOOH})$, oxidation of adsorbed material predominates at first and, later, oxidation of formic acid diffusing to the interface makes a contribution. The oxidation of the

electrode is, however, considerably retarded. At higher current densities, oxidation of adsorbed material again predominates at first but later oxidation of the electrode itself makes a significant contribution to the current. Oxidation of formic acid diffusing to the electrode is relatively minor.

Using this technique, one finds that for every site (the number of sites was determined from hydrogen adsorption) two electrons are required to oxidize anodically the adsorbed material. The maximum sorption of the blocking substance corresponds to between 300 and 350 $\,\mu\,e/cm^2$ of anodic charge (depending on what assumption one makes for the relation between real and apparent area). Studies of the over-all adsorption process are being continued and comparison with the behavior of other compounds is planned.

VI. TECHNICAL MEMORANDA AND PUBLICATIONS

The following technical memoranda were issued during this report period:

Technical Memorandum No. 6: "Surface Oxidation of Gold", accepted by the Journal of the Electrochemical Society.

Technical Memorandum No. 7: "Hydrogen Evolution at Dilute Platinum and Palladium Amalgam Electrodes", accepted by Transactions of the Faraday Society.

Technical Memorandum No. 8: "Adsorption and Oxidation of HCOOH on Smooth Pt Electrodes in ${\rm HClO}_4$ Solutions", accepted by Journal of Physical Chemistry.

Technical Memorandum No. 9: "Activity Coefficients of Liquid Indium-Mercury Amalgams at $25^{\circ}\mathrm{C}$ ", accepted by Journal of Physical Chemistry.

Technical Memorandum No. 10: "Hydrogen Evolution at a Dropping Indium Amalgam Electrode", submitted to Transactions of the Faraday Society.

TECHNICAL REPORT DISTRIBUTION LIST

Contract No. Nonr 3765 (OO)

Commanding Officer Office of Naval Research Branch Office 230 N. Michigan Avenue Chicago I, Illinois (1)	Harry Diamond Laboratories Washington 25, D. C. Attn: Library (1)
Commanding Officer Office of Naval Research Branch Office 207 West 24th Street New York 11, New York (1)	Office, Chief of Research & Development Department of the Army Washington 25, D. C. Attn: Physical Sciences Division(1)
Commanding Officer Office of Naval Research Branch Office 1030 East Green Street Pasadena I, California (1)	Chief, Bureau of Ships Department of the Navy Washington 25, D. C. Attn: Code 342A (2)
Commanding Officer Office of Naval Research Branch Office Box 39, Navy #100, F.P.O. New York, New York (7)	Technical Library, DLI-3 Bureau of Naval Weapons Department of the Navy Washington 25, D. C. (4)
Director, Naval Research Laboratory Washington 25, D. C. Attn: Technical Information Officer (6) Chemistry Division (2)	Defense Documentation Center Cameron Station Alexandria, Virginia (20)
Chief of Naval Research Department of the Navy Washington 25, D. C. Attn: Code 425 (2)	Commanding Officer U. S. Army Electronics Research and Development Laboratory Attn: SELRA/DR Fort Monmouth, New Jersey 07703 (1)
DDR&E Technical Library Room 3C-128, The Pentagon Washington 25, D. C. (1)	Naval Radiological Defense Laboratory San Francisco 24, California Attn: Technical Library (1)
Department of the Army Supply & Maintenance Command Maintenance Readiness Division Washington 25, D. C. Attn: Technical Director (1)	Naval Ordnance Test Station China Lake, California Attn: Head, Chemistry Div. (1)
U. S. Army Natick Laboratories Clothing & Organic Materials Division Natick, Massachusetts Attn: Associate Director (1)	Commanding Officer Army Research Office Box CM, Duke Station Durham, North Carolina Attn: CRD-AA-IP (1)

Atomic Energy Commission Division of Research Chemistry Programs Washington 25, D. C.	(1)	Dr. Howard L. Recht Astropower, Inc. 2968 Randolph Avenue Costa Mesa, California	(1)
Atomic Energy Commission Division of Technical Informat Extension Post Office Box 62 Oak Ridge, Tennessee	ion (1)	Mr. L. R. Griffith California Research Corporati 576 Standard Avenue Richmond, California	.on (1)
Commanding Officer U.S. Army Chemical Research Development Laboratories		Dr. Ralph G. Gentile Monsanto Research Corporatio Boston Laboratories Everett 49, Massachusetts	on (1)
Attn: Librarian Edgewood Arsenal, Maryland Commanding Officer ONR Branch Office	(1)	Mr. Ray M. Hurd Texas Research Associates 1701 Guadalupe Street Austin I, Texas	(1)
495 Summer Street Boston 10, Massachusetts Director, ARPA Attn: Dr. J. H. Huth Material Sciences	(1)	Dr. C. E. Heath Esso Research & Engineering Company Box 51	(1)
Room 3DI55 The Pentago Washington 25, D.C. Dr. S. Schuldiner Naval Research Laboratory Co	(4) ode 6160	Mr. R. J. Flannery American Oil Company Whiting Laboratories Post Office Box 431	(1)
Washington 25, D. C. Dr. A. B. Scott Department of Chemistry Oregon State University Corvallis, Oregon	(1)		(l)
Inspector of Naval Material 495 Summer Street Boston 10, Massachusetts	(1)	Dr. E. A. Oster General Electric Company, DE Lynn, Massachusetts	
Mr. R. A. Osteryoung Atomics International Canuga Park, California Dr. David M. Mason	(1)	Dr. R. R. Heikes Solid State Phenomena Dept. Westinghouse Electric Corpora Pittsburgh, Pennsylvania	ation (l)
Stanford University Stanford, California	(1)	Professor Herman P. Meissner Massachusetts Institute of Technology Cambridge 39, Massachusetts	

Mr. Donald P. Snowden General Atomic Post Office Box 608 San Diego 12, California	(1)	Dr. B. R. Sundheim Department of Chemistry New York University New York 3, New York	(1)
Mr. C. Tobias Chemistry Department University of California Berkeley, California	(1)	Dr. E. M. Cohn NASA Code RPP 1512 H Street, N. W. Washington 25, D. C.	(1)
Mr. Y.L. Sandler Westinghouse Research Labor Pittsburgh, Pennyslvania	atories (1)	Dr. E. Yeager Department of Chemistry Western Reserve University	
Dr. Paul Delahay Department of Chemistry Louisiana State University Baton Rouge, Louisiana	(1)	Or. V. 1. Matkovich The Carborundum Company	(1)
Dr. W. J. Hamer Electrochemistry Section National Bureau of Standards Washington 25, D.C.	(1)	Dr. A. M. Zwickel Department of Chemistry Clark University Worcester, Massachusetts	(1)
Dr. Herbert Hunger Power Sources Division U.S. Army Signal Research & Development Laboratory Fort Monmouth, New Jersey	(1)	Dr. Michael O'Keefe Department of Chemistry Arizona State University Tempe, Arizona	(1)
Dr. T. P. Dirkse Department of Chemistry Calvin College Grand Rapids, Michigan	(1)	Lockheed Aircraft Corporation Missiles and Space Division Technical Information Center 3251 Hanover Street Palo Alto, California	(1)
Dr. George J. Janz Department of Chemistry Rensselaer Polytechnic Institu Troy, New York	nte (1)	Dr. G. C. Szego Institute for Defense Analysis 1666 Connecticut Avenue, N. W Washington 9, D. C.	'. (1)
Mr. N. F. Blackburn E.R.D.L. Materials Branch Fort Belvoir, Virginia	(1)	Dr. R. F. Baddour Department of Chemistry Massachusetts Institute of Technology	
Mr. W. M. Lee, Director Contract Research Department Pennsalt Chemicals Corporati 900 First Avenue	on	Cambridge 39, Massachusetts	(1)
King of Prussia, Pennsylvania	(2)		

Mr. T. W. Cushing, Manager Military Service Department Engelhard Industries, Inc. 113 Astor Street Newark, New Jersey (1)

Thompson Ramo Wooldridge Inc.
23555 Euclid Avenue
Cleveland 17, Ohio
Attn: J. Ed Taylor
Associate Director, RD&E

Aerospace Corporation
Post Office Box 95085
Los Angeles 45, California
Attn: Library Technical
Documents Group (1)

Dr. Galen R. Frysinger
Electric Power Branch
E.R.D.L.
Fort Belvoir, Virginia (1)

Mr. Robert Post
Lewis Laboratories
NASA
21000 Brook Park Road
Cleveland 35, Ohio (1)

Mr. Nathan Kaplan, Chief Power Supply Branch 940 Harry Diamond Laboratories Washington 25, D.C. (1)

Mr. R. Comyn Power Supply Branch 940 Harry Diamond Laboratories Washington 25, D.C. (1)

UNCLASSIFIED

UNCLASSIFIED